Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1AV2062A **SIMOTICS GP - 63 M - IM B3 - 2p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
230	Δ	50	0.18	-/-	0.96	2850	0.6	60.4	59.4	53.7	0.78	0.69	0.54	4.5	2.2	2.7	IE2
400	Y	50	0.18	-/-	0.55	2850	0.6	60.4	59.4	53.7	0.78	0.69	0.54	4.5	2.2	2.7	IE2
460	Y	60	0.21	-/-	0.53	3450	0.6	64.0	62.0	57.0	0.78	0.69	0.55	4.9	2.3	3.1	IE2
460	Y	60	0.18	-/-	0.49	3475	0.5	64.0	60.8	54.6	0.72	0.62	0.50	5.3	2.7	3.6	IE2

IM B3 / IM 1001	FS 63 M	kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 12.7 s | 15.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	/ dB(A) 2)	/ dB(A) 2)	Vibration severity grade	A
Moment of inertia	0.0002 kg m²		Insulation	155(F) to 130(B)
Bearing DE | NDE	6201 2Z C3	6201 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	
DI MC LVM		DT Configurator		*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*

SIEMENS

document type	document status	customer
datasheet	released	
title	document number	
1LE1001-0BA22-2AA4-Z		
H03		

rev.	creation date	language	Page
01	2021-09-01 14:52	en	1/2

© Siemens AG 2021

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1AV2062A **SIMOTICS GP - 63 M - IM B3 - 2p**

Special design

H03	Condensation drain holes in end shield

Notes:

responsible dep.	technical reference	created by	approved by	
DI MC LVM		DT Configurator		*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*

SIEMENS	document type: datasheet	document status: released	customer	
	title: 1LE1001-0BA22-2AA4-Z	document number		
© Siemens AG 2021	H03	rev.: 01	creation date: 2021-09-01 14:52	language: en / Page: 2/2

Confid® ıtre de secret d'entreprise. Tous droits ®servés.
Comunicado como secreto empresarial. Reservados todos os direitos.
[ra,ar,ıdo y o tra,ıtes,ıdo ,ıtelectual ,ıdustrial.
Confiado como secreto de empresa. Nos reservamos todos los derechos.

Weitergabe sowie Vervielfältigung, Verbreitung und/oder Bearbeitung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung, Gebrauchsmuster- oder Geschmacksmustereintragung vorbehalten

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for the payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.



Tolerance	Surface	Material	Weight	Scale
			-	mm
1LE1001-0BA22-2AA4-Z H03	Author Creator DTK Approval Department	Dimensional drawing MaÇzeichnung		
	Change Order	MLFB		Doc Type /
SIEMENS	Doc State 9/1/21	Item No		Paper Size A3
	Revision Index RS	Doc No		1st Language en 2nd Language de
© Siemens AG 2018	Project No -	Ref No -		Sheet 1 of 1